

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### T300



Model	T314-3	T314-4	T314-5
Deck	6'5" X 14'	6'5" X 14'	6'5" X 14'
Deck Type	2" X 12" Douglas Fir	2" X 12" Douglas Fir	2" X 12" Douglas Fir
Deck Height	18" Loaded	18" Loaded	18" Loaded
Axles	2 - 3,500 lb.	2 - 5,200 lb.	2 - 6,000 lb.
Tires	ST205-75-R15	ST225-75-R15	ST235-80-R16
Brakes	Electric	Electric	Electric
Hitch	Adjustable Pintle Ring	Adjustable Pintle Ring	Adjustable Pintle Ring
Jack	2,000 lb. Swivel	2,000 lb. Swivel	5,000 lb. Swivel
Ramps	Adjustable 18" X 62" Tilt Up	Adjustable 18" X 62" Tilt Up	Adjustable 18" X 62" Tilt Up
GVW	7,500 lb.	10,000 lb.	13,000 lb.
Max Capacity	6,000 lb.	8,150 lb.	11,000 lb.

### OPTIONS

- **Deck:** 1/8" or 3/16" Diamond Plate
- **Deck Length:** (+/-) 2 ft. Increments Up To 20'
- **Deck Width:** Up To 82"
- **Wheels:** Chrome
- **Tires:** LT235-85-R16 E or G Rated
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** 2" or 2 5/16" Ball Coupler up to 12,000 lb. GVW
- **Jack:** 7,000 lb. Drop Foot
- **Ramps:** Wood filled and tapered ramps
- **Accessories:** Spare tire with or without mount, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### T400



Model	T412-4	T412-5
Deck	6' X 12'	6' X 12'
Deck Type	2" X 12" Douglas Fir	2" X 12" Douglas Fir
Deck Height	15" Loaded with Climb Angle <10 degrees	15" Loaded with Climb Angle <10 degrees
Axles	1 - 5,200 lb	1 - 6,000 lb.
Tires	ST225-75-R15	ST235-80-R16
Brakes	Electric	Electric
Hitch	Adjustable Pintle Ring	Adjustable Pintle Ring
Jack	2,000 lb. Swivel	2,000 lb. Swivel
Ramps	Adjustable 18" X 62" Tilt Up	Adjustable 18" X 62" Tilt Up
GVW	5,500 lb.	6,500 lb.
Max Capacity	4,000 lb.	5,000 lb.

### OPTIONS

- **Deck:** 1/8" or 3/16" Diamond Plate
- **Deck Length:** Up to 16'
- **Deck Width:** Up to 80"
- **Tires:** ST235-85-R16 G614 (on T412-5)
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** 2 5/16" Ball Coupler
- **Jack:** 5,000 lb. Swivel
- **Bumper:** 8" Rear steel tapered extension
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308  
 PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)  
 FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### T400-5D



Model	T412--5D	T414-5D	T416-6D
<b>Box</b>	6' X 12' with 2' High Sides	6' X 14' with 4' High Sides	6' X 16' with 4' High Sides
<b>Hoist</b>	Rugby LR416, 5 ton with Electric Pump and Battery	Rugby LR416, 5 ton with Electric Pump and Battery	Rugby LR25, 8 ton with Electric Pump and Battery
<b>Floor</b>	1/8" Smooth Steel	1/8" Smooth Steel	1/8" Smooth Steel (at 34")
<b>Sides</b>	14 Ga. Smooth Steel Double Back Doors	14 Ga. Smooth Steel Double Back Doors	14 Ga. Smooth Steel Double Back Doors
<b>Axles</b>	2 - 6,000 lb.	2 - 6,000 lb.	2 - 7,000 lb.
<b>Tires</b>	ST235-80-R16	ST235-80-R16	ST235-85-R16 G614
<b>Brakes</b>	Electric	Electric	Electric
<b>Hitch</b>	Adjustable Pintle Ring	Adjustable Pintle Ring	Adjustable Pintle Ring
<b>Jack</b>	5,000 lb. Swivel	7,000 lb. Drop Foot	10,000 lb. Drop Foot
<b>GVW</b>	13,000 lb.	13,000 lb.	16,000 lb.
<b>Max Capacity</b>	9,000 lb.	9,000 lb.	11,000 lb.

### OPTIONS

- **Hoist:** LR26 12-Ton
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** Fifth Wheel or Gooseneck
- **Jack:** 12,000 lb. Drop Foot
- **Ramps:** 15" X 6' Slide In with Under Mount Storage Compartment
- **Tie Downs:** D-rings in bed upon request
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### TT400



<b>Model</b>	<b>TT414</b>
<b>Deck</b>	80" Wide Main Frame w/75" X 14' Inner Frame Tilt
<b>Deck Type</b>	2" X 12" Douglas Fir
<b>Deck Height</b>	20" Loaded
<b>Axles</b>	2 - 5,200 lb. 4" Drop
<b>Tires</b>	ST225-75-R15
<b>Brakes</b>	Electric
<b>Hitch</b>	Adjustable Pintle Ring
<b>Jack</b>	2,000 lb. Swivel
<b>GVW</b>	10,000 lb.
<b>Max. Capacity</b>	8,000 lb.

### OPTIONS

- **Deck:** 1/8" or 3/16" Diamond Plate
- **Deck Length:** (+/-) 2 ft. Increments up to 18'
- **Deck Width:** Up to 82"
- **Axles:** 6,000 lb. (GVW: 13,000 lb., Max. Capacity: 11,000 lb.), 7,000 lb. (GVW: 13,000 lb., Max. Capacity: 11,000 lb.)
- **Tires:** ST235-80-R16
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** 2 5/16" Ball Coupler
- **Optional:** 8" Rear steel tapered extension
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### T500



<b>Model</b>	<b>T516</b>
<b>Deck</b>	6' 10" X 16' Flatbed
<b>Deck Type</b>	2" X 12" Douglas Fir
<b>Deck Height</b>	25" Loaded
<b>Axles</b>	2 - 6,000 lb.
<b>Tires</b>	ST235-80-R16
<b>Brakes</b>	Electric
<b>Hitch</b>	Adjustable Pintle Ring
<b>Jack</b>	5,000 lb. Swivel
<b>Ramps</b>	18" X 62" Fold-up
<b>GVW</b>	13,000 lb.
<b>Max Capacity</b>	10,800 lb.

### OPTIONS

- **Deck:** 1/8" or 3/16" Diamond Plate
- **Deck Length:** (+/-) 2 ft. Increments Up To 20' (Note: 20' Trailers only available in steel deck)
- **Axles:** 7,000 lb. and 8,000 lb.
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** 2 5/16" Ball Coupler and/or Gooseneck
- **Jack:** 7,000 or 12,000 lb. Drop Foot
- **Ramps:** Slide-in
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### T800



Model	T820-5	T822-7
Deck	8' X 20' including 5' Beaver tail	8' X 22' including 5' Beaver tail
Deck Type	2" X 12" Douglas Fir	2" X 12" Douglas Fir
Deck Height	35" Loaded	35" Loaded
Axles	2 - 6,000 lb	2 - 8,000 lb
Tires	ST235-80-R16	ST215-75-R17.5 G114
Brakes	Electric	Electric
Hitch	Adjustable Pintle Ring	Adjustable Pintle Ring
Jack	12,000 lb. Drop Foot	12,000 lb. Drop Foot
Ramps	Adj. 18" X 62" Fold-up, Spring Assist	Adj. 18" X 62" Fold-up, Spring Assist
GVW	13,500 lb.	18,000 lb.
Max Capacity	10,300 lb.	14,000 lb.

### OPTIONS

- **Deck:** 1/8" or 3/16" Diamond Plate
- **Tires:** LT235-85-R16 G on 7,000 lb. Axle.
- **Brakes:** Surge/Hydraulic (NOTE: Surge brakes may be deemed illegal in certain applications), Electric/Hydraulic, Disk Brakes on -5 Model and Above
- **Hitch:** Adjustable Gooseneck Coupler, 2 5/16" Ball coupler (T820-5)
- **Model Configurations:** Flatbeds available
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308  
PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)  
FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### TD800



<b>Model</b>	<b>TD824-10</b>
<b>Deck</b>	8' X 24' Including 5' Beavertail
<b>Deck Type</b>	2" X 12" Douglas Fir
<b>Deck Height</b>	35" Loaded
<b>Axles</b>	2 - 10,000 lb.
<b>Tires</b>	ST235-80R16
<b>Brakes</b>	Electric
<b>Hitch</b>	Adjustable Pintle Ring
<b>Jack</b>	12,000 lb. Drop Foot
<b>Ramps</b>	Adjustable 18" X 62" Fold-up, spring assist
<b>GVW</b>	25,000 lb.
<b>Max Capacity</b>	20,000 lb.

### OPTIONS

- **Deck:** 2" X 12" Apitong or 1/8" or 3/16" Diamond Plate
- **Tires:** 235-85-R16 G on 10 and 12 Ton Models, 215-75-R17.5 on 15 Ton or Larger Models
- **Brakes:** Air w/ABS on 15,000 and 20,000 lb. axles
- **Hitch:** Gooseneck or Fifth Wheel
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes

## FLEMING TRAILERS, INC.

17033 N 63rd AVE, GLENDALE, AZ. 85308

PHONE: 602-938-2513 (Best time to call: 7:00AM - 4:00PM MST)

FAX: 602-439-2470, Email: [david@flemingtrailers.com](mailto:david@flemingtrailers.com)

### TDT800



Model	TDT824-10	TDT824-A20
Deck	8' X 24' Tilt Bed	8' X 24' Tilt Bed
Deck Type	2" X 12" Douglas Fir	2" X 12" Apitong
Deck Height	35" Loaded	35" Loaded
Axles	2 - 10,000 lb.	2 - 20,000 lb.
Tires	ST235-80-R16	215/75/R17.5 16 Ply
Brakes	Electric	Air w/ABS
Hitch	Adjustable Pintle Ring	Adjustable Pintle Ring
Jack	12,000 lb. Drop Foot	12,000 lb. Drop Foot
Bumper	7" Channel Bumper on Rear	7" Channel Bumper on Rear
Suspension	Dexter 20,000 lb.	9700 Series, 50,000 lb. Hutch
Dampering Cylinder	3 X 16 Hydraulic	4 X 16 Hydraulic
GVW	25,900 lb	49,500 lb.
Max Capacity	20,000 lb.	40,000 lb.

### OPTIONS

- **Deck:** 2" x 12" Apitong or 1/8" or 3/16" Diamond Plate
- **Deck Length:** (+/-) 2 ft. Increments
- **Axles:** 9,000 lb. and 15,000 lb.
- **Brakes:** Air w/ABS on 10, 15, and 20,000 lb. Axles
- **Hitch:** Fifth Wheel or Gooseneck
- **Ramp:** 12" Tapered Auto Flap or 6'6" Collapsible ICC Bumper
- **Accessories:** Spare tire with or without mounts, in-tongue storage compartment, custom fabricated containers/boxes, and various size buyers boxes